



VARIA




VARIA T

Installation of the operator bracket to the counter-frame



Installation of the chain coupling to the mobile wing



Installation of the apricolor varia operator to the counter-frame



# APRICOLOR VARIA

i222


Chain operator for bottom-hinged and outward-opening windows.

## TECHNICAL DATA

POWER SUPPLY	230 Vca - 24 Vcc
ABSORBED POWER	150 W - 40 W
ABSORBED CURRENT	0,8A in ca/1,8 in cc
THRUST FORCE	150 N
TRACTION FORCE	300 N
ADJUSTABLE STROKES	from 90 to 400 mm
SHIFTING SPEED	40 mm/s
FRONT ADJUSTMENT	max. 10 mm
PARALLEL CONNECTION	YES
OVERLOAD PROTECTION	100° C (only 230 V versions)
CAPACITOR	4 µF
BUILT-IN RELAY	YES
LIGHT INDICATOR	YES
REMOVABLE TERMINAL BOARD	YES
PROTECTION DEGREE	IP20
OPERATOR WEIGHT	1.7 Kg



NOTE: Use of the Varia actuator still requires (compulsorily) the application of safety arms on the windows.





**Exclusive quick-fit system** securing the operator to the frame.

**Apricolor VARIA is an electromechanical chain operator** with internal nylon magazine.

It is suitable for bottom-hinged and outward-opening applications, and features an adjustable stroke from 90 to 400 mm.

230 V and 24 V operation.  
It can be connected in parallel.  
The chain is rust-proof thanks to the Dacro-met coating.

Apricolor VARIA T is designed for twin-mounting on single windows with width over 1600 mm. Apricolor VARIA T stands out for its overload protection, shared between the two parallel-connected operators. If one of the two trips, the other stops its motion, thus protecting the frame from torsional stresses.

ITEM NUMBER	CHAIN OPERATORS	POWER SUPPLY	NOTES
43503/021	APRICOLOR VARIA RAL9005 Black	230 Vca	Screw Kit (conventional fitting) included
43503/022	APRICOLOR VARIA RAL9010 White	230 Vca	Screw Kit (conventional fitting) included
43503/023	APRICOLOR VARIA RAL9006 Grey	230 Vca	Screw Kit (conventional fitting) included

ITEM NUMBER	CHAIN OPERATOR PARALLEL CONNECTION ON THE SAME FRAME	POWER SUPPLY	NOTES
43503/024	APRICOLOR VARIA T RAL9005 Black (for installation with another Varia T, >1,600 mm-wide windows)	230 Vca	Screw Kit (conventional fitting) included
43503/025	APRICOLOR VARIA T RAL9010 White (for installation with another Varia T, >1,600 mm-wide windows)	230 Vca	Screw Kit (conventional fitting) included
43503/026	APRICOLOR VARIA T RAL9006 Grey (for installation with another Varia T, >1,600 mm-wide windows)	230 Vca	Screw Kit (conventional fitting) included

ITEM NUMBER	CHAIN OPERATORS	POWER SUPPLY	NOTES
43502/001 *	APRICOLOR VARIA RAL9005 Black	24 Vcc	Screw Kit (conventional fitting) included
43502/002 *	APRICOLOR VARIA RAL9010 White	24 Vcc	Screw Kit (conventional fitting) included
43502/003 *	APRICOLOR VARIA RAL9006 Grey	24 Vcc	Screw Kit (conventional fitting) included

ITEM NUMBER	DESCRIPTION	NOTES
43501/050	Extension Pin for chain connection - 38mm	For wood/PVC frames Minimum pack 10 pcs
43503/055 *	SCREW KIT conventional fitting system for outward- opening windows	Minimum pack 10 pcs
43503/056 *	SCREW KIT conventional fitting system for bottom-hinged windows	Minimum pack 10 pcs

\* Until stocks last

NOTE: for motor control unit selection, please refer to the "Home automation" chapter.

NOTE: All prices are subject to variation.