



ALLIGATOR Ready Set

Transportband- Verbindungssystem für Bandstärken von 1,5 - 6,4 mm

Conveyor Belt Fastening System for Belts 1,5 - 6,4 mm thick

Système d'agrafage pour bandes transporteuses d'épaisseur 1,5 - 6,4 mm

Verbindergroße Fastener Size Taille des agrafes	Für Transportbänder bis zu... N/mm Festigkeit For Belts with a Tensile Strength of up to... N/mm Pour bandes tranporteuses à résistance de rupture jusqu'à... N/mm	empf. Bandstärkenbereich Belt Thickness Range Épaisseur de bandes recommandée mm	empf. kleinster Trommel-Ø rec. min. Pulley-Ø Ø tambour mini.rec. mm
RS62	200	1,5 - 3,2	50
RS125	315	3,2 - 4,8	75
RS187	400	4,8 - 6,4	100

Inhalt: Jeder J-Karton enthält 4 komplette Verbindungen für die angegebene Bandbreite.

Content: Each J-box contains 4 Sets Lacing for the Belt Width specified.

Contenu: Chaque boîte J contient 4 jeux complets de jonction pour la largeur de bande spécifiée.

Stahl verzinkt / Galvanized Steel Acier galvanisé

Bestell-Nr. Order-No. No. de réf.	Bandbreite Belt Width Larg. de bande mm	Gewicht Weight Poids kg
RS62J12/300NC	300	0,61
RS62J24/600NC	600	1,22
RS62J32/800NC	800	1,64
RS62J40/1000NC	1000	2,05
RS62J47/1200NC	1200	2,44
RS62J59/1500NC	1500	3,05
RS125J12/300NC	300	0,91
RS125J24/600NC	600	1,78
RS125J32/800NC	800	2,43
RS125J40/1000NC	1000	3,04
RS125J47/1200NC	1200	3,65
RS125J59/1500NC	1500	4,56
RS187J12/300NC	300	1,16
RS187J24/600NC	600	2,69
RS187J32/800NC	800	3,36
RS187J40/1000NC	1000	4,20
RS187J47/1200NC	1200	5,33
RS187J59/1500NC	1500	6,26

Rostfrei / Stainless Inoxydable

Bestell-Nr. Order-No. No. de réf.	Bandbreite Belt Width Larg. de bande mm	Gewicht Weight Poids kg
RS62SJ12/300NCS	300	0,61
RS62SJ24/600NCS	600	1,22
RS62SJ32/800NCS	800	1,64
RS62SJ40/1000NCS	1000	2,05
RS62SJ47/1200NCS	1200	2,44
RS62SJ59/1500NCS	1500	3,05
RS125SJ12/300NCS	300	0,91
RS125SJ24/600NCS	600	1,78
RS125SJ32/800NCS	800	2,43
RS125SJ40/1000NCS	1000	3,04
RS125SJ47/1200NCS	1200	3,65
RS125SJ59/1500NCS	1500	4,56
RS187SJ12/300NCS	300	1,16
RS187SJ24/600NCS	600	2,69
RS187SJ32/800NCS	800	3,36
RS187SJ40/1000NCS	1000	4,20
RS187SJ47/1200NCS	1200	5,33
RS187SJ59/1500NCS	1500	6,26

25 Verbindersets (ohne Kupplungsstäbe) · 25 Fastener Sets (without Hinge Pins) · 25 Jeux de jonction (sans axe)

RS62-47/1200-25	1200	13,50	RS62S-47/1200-25	1200	17,50
RS125-47/1200-25	1200	18,70	RS125S-47/1200-25	1200	18,70
RS187-47/1200-25	1200	27,50	RS187S-47/1200-25	1200	27,50

MegAlloy

Bestell-Nr. Order-No. No. de réf.	Inhalt Content Contenu	Gewicht Weight Poids kg
125MA*	8 X 300 mm	1,9
187MA*	8 X 300 mm	2,6

Extra Klammern, rostfrei · Extra Staples, stainless Crampons supplémentaires, inoxydables

Bestell-Nr. Order-No. No. de réf.	Verbindergroße Fastener size Taille d'agrafe	Inhalt Content Contenu	Gewicht Weight Poids kg
S125	125	990	0,41
S187	187	990	0,46

* ohne Kupplungsdrähte / without hinge pins / sans tige de jonction

Montage von MegAlloy Verbindern mit ST4-5 Block (grün) und Klammermagazin C150.
Installation of MegAlloy fasteners with ST4-5 block (green) and staple dispenser C150.
Installation des agrafes MegAlloy avec bloc ST4-5 (vert) et chargeur de crampons C150.

Kupplungsdrähte Hinge Material Axes de jonction	Bestell-Nr. Order-No. No. de réf.	Ø mm	Verbindergröße Fastener Size Taille d'agrafe	Inhalt Content Contenu	Gewicht Weight Poids kg
NC Nylostahl Kabel Nylo Stainless Cable Câble nyloacier	NC62-X	2,0	RS62	3 m	0,05
	NC62-C			30 m	0,45
	NC1-X	3,6	RS125	3 m	0,09
	NC1-C			30 m	0,77
	NC187-X	5,2	RS187	3 m	0,09
	NC187-C			30 m	2,17
NCS* Nylorostfrei Kabel Nylo Stainless Cable Câble nyloinox	NCS62-X	2,0	RS62	3 m	0,05
	NCS62-C			30 m	0,45
	NCS1-X	3,6	RS125	3 m	0,09
	NCS1-C			30 m	0,77
	NCS187-X	5,2	RS187	3 m	0,09
	NCS187-C			30 m	2,17
SP Federstahl Spring Steel Acier à ressort * Bandbreite (mm) * Belt Width (mm) * Largeur de bande (mm)	SP62-1000	2,0	RS62	10 X 1000* mm	0,32
	SP62-1200			10 X 1200* mm	0,37
	SP62-1500			10 X 1500* mm	0,40
	SP1-1000	3,6	RS125	10 X 1000* mm	0,68
	SP1-1200			10 X 1200* mm	0,87
	SP1-1500			10 X 1500* mm	1,00
	SP2-1000	4,7	RS187	10 X 1000* mm	1,23
	SP2-1200			10 X 1200* mm	1,55
	SP2-1500			10 X 1500* mm	1,80
	SS* Federstahl rostfrei Stainless Spring Steel Acier inoxydable à ressort * Bandbreite (mm) * Belt Width (mm) * Largeur de bande (mm)	SS62-1000	2,0	RS62	10 X 1000* mm
SS62-1200		10 X 1200* mm			0,37
SS62-1500		10 X 1500* mm			0,42
SS1-1000		3,6	RS125	10 X 1000* mm	0,68
SS1-1200				10 X 1200* mm	0,87
SS1-1500				10 X 1500* mm	1,00
SS2-1000		4,7	RS187	10 X 1000* mm	1,23
SS2-1200				10 X 1200* mm	1,55
SS2-1500				10 X 1500* mm	1,95
Kupplungsstab-Sicherungs- scheiben		62-RET-50		RS62	50
	125-RET-50		RS125	50	0,05
Hinge Pin Retaining Washers Rondelles de butée pour axes de jonction	187-RET-50		RS187	50	0,06

* leicht magnetisch / slightly magnetic / faiblement magnétique

Hinge Pin Selection Chart

Wide selection makes it easy to match the correct hinge pin to the needs of your application.

Nylon Covered Steel Cable (NC): Nylon covering reduces corrosion and simplifies hinge pin insertion.

Nylon Covered Stainless Steel Cable (NCS): For greater corrosion resistance.

Steel Spring Wire (SP): For flat belt conveyors carrying abrasive or gritty materials.

Stainless Steel Spring Wire (SS): For use with stainless steel fasteners.

Hinge Pins (Extra)

For 62				For 62							
Coil Length		Ordering Number		Belt Width		Ordering Number (Packages of 10 Pins)					
M	Foot	NC62 Nylon Covered Steel Cable	NCS62 Nylon Covered Stainless Cable	mm	in.	SP62 Steel Spring Wire Pins	SS62 300 Series Stainless Spring Wire Pins				
3	10	NC62-X	NCS62-X	300	12	SP62-12/300	SS62-12/300				
30	100	NC62-C	NCS62-C	400	16	SP62-16/400	SS62-16/400				
				450	18	SP62-18/450	SS62-18/450				
				500	20	SP62-20	SS62-20				
				600	24	SP62-24/600	SS62-24/600				
				750	30	SP62-30/750	SS62-30/750				
				900	36	SP62-36/900	SS62-36/900				
				1050	42	SP62-42	SS62-42				
				1200	48	SP62-48	SS62-48				
				1350	54	SP62-54	SS62-54				
				1500	60	SP62-60	SS62-60				
For 125				For 125							
Coil Length		Ordering Number		Belt Width		Ordering Number (Packages of 10 Pins)					
M	Foot	NC1 Nylon Covered Steel Cable	NCS1 Nylon Covered Stainless Cable	mm	in.	SP1 Steel Spring Wire Pins	SS1 300 Series Stainless Spring Wire Pins				
3	10	NC1-X	NCS1-X	400	16	SP1-16/400	SS1-16/400				
30	100	NC1-C	NCS1-C	450	18	SP1-18/450	SS1-18/450				
				500	20	SP1-20	SS1-20				
				600	24	SP1-24/600	SS1-24/600				
				750	30	SP1-30/750	SS1-30/750				
				900	36	SP1-36/900	SS1-36/900				
				1050	42	SP1-42	SS1-42				
				1200	48	SP1-48	SS1-48				
				1500	60	SP1-60	SS1-60				
				For 187				For 187			
				Coil Length		Ordering Number		Belt Width		Ordering Number (Packages of 10 Pins)	
M	Foot	NC187 Nylon Covered Steel Cable	NCS187 Nylon Covered Stainless Cable	mm	in.	SP2 Steel Spring Wire Pins	SS2 300 Series Stainless Spring Wire Pins				
3	10	NC187-X	NCS187-X	450	18	SP2-18/450	SS2-18/450				
30	100	NC187-C	NCS187-C	500	20	SP2-20	SS2-20				
				600	24	SP2-24/600	SS2-24/600				
				750	30	SP2-30/750	SS2-30/750				
				900	36	SP2-36/900	SS2-36/900				
				1050	42	SP2-42	SS2-42				
				1200	48	SP2-48	SS2-48				
				1500	60	SP2-60	SS2-60				

Alligator® Ready Set™ Staple Fastener System

Selection Charts

Fasteners

Belt Width		Ordering Number		Belt Width		Ordering Number	
mm	in.	With Nylon Covered Steel Cable Pins (NC)	With Steel Spring Wire Pins (SP)	mm	in.	With Stainless Spring Wire Pins (SS)	With Nylon Covered Stainless Cable Pins (NCS)
RS62 Steel				RS62 Stainless (Type 316)			
300	12	RS62J12/300NC	RS62J12/300SP	300	12	RS62SJ12/300SS	RS62SJ12/300NCS
400	16	RS62J16/400NC		400	16		
450	18	RS62J18/450NC	RS62J18/450SP	450	18	RS62SJ18/450SS	RS62SJ18/450NCS
500	20	RS62J20/500NC	RS62J20/500SP	500	20	RS62SJ20/500SS	
600	24	RS62J24/600NC	RS62J24/600SP	600	24	RS62SJ24/600SS	RS62SJ24/600NCS
750	30	RS62J30/750NC	RS62J30/750SP	750	30	RS62SJ30/750SS	RS62SJ30/750NCS
900	36	RS62J36/900NC	RS62J36/900SP	900	36	RS62SJ36/900SS	RS62SJ36/900NCS
1050	42	RS62J42NC	RS62J42SP	1050	42	RS62SJ42SS	
1200	48	RS62J48NC	RS62J48SP	1200	48	RS62SJ48SS	RS62SJ48NCS
1500	60	RS62J60NC	RS62J60SP	1500	60	RS62SJ60SS	RS62SJ60NCS
RS125 Steel				RS125 Stainless (Type 316)			
100	4	RS125J4NC*		100	4		
250	10	RS125J10NC		250	10		RS125SJ10NCS
300	12	RS125J12/300NC		300	12	RS125SJ12/300SS	RS125SJ12/300NCS
350	14	RS125J14NC		350	14	RS125SJ14SS	RS125SJ14NCS
400	16	RS125J16/400NC	RS125J16/400SP	400	16	RS125SJ16/400SS	RS125SJ16/400NCS
450	18	RS125J18/450NC	RS125J18/450SP	450	18	RS125SJ18/450SS	RS125SJ18/450NCS
500	20	RS125J20/500NC	RS125J20/500SP	500	20	RS125SJ20/500SS	RS125SJ20/500NCS
600	24	RS125J24/600NC	RS125J24/600SP	600	24	RS125SJ24/600SS	RS125SJ24/600NCS
750	30	RS125J30/750NC	RS125J30/750SP	750	30	RS125SJ30/750SS	RS125SJ30/750NCS
900	36	RS125J36/900NC	RS125J36/900SP	900	36	RS125SJ36/900SS	RS125SJ36/900NCS
1050	42	RS125J42NC	RS125J42SP	1050	42	RS125SJ42SS	RS125SJ42NCS
1200	48	RS125J48NC	RS125J48SP	1200	48	RS125SJ48SS	RS125SJ48NCS
1500	60	RS125J60NC	RS125J60SP	1500	60	RS125SJ60SS	RS125SJ60NCS
RS187 Steel				RS187 Stainless (Type 316)			
100	4	RS187J4NC*		100	4		
300	12	RS187J12/300NC		300	12		RS187SJ12/300NCS
400	16	RS187J16/400NC		400	16	RS187SJ16/400SS	RS187SJ16/400NCS
450	18	RS187J18/450NC	RS187J18/450SP	450	18	RS187SJ18/450SS	RS187SJ18/450NCS
500	20	RS187J20/500NC	RS187J20/500SP	500	20	RS187SJ20/500SS	RS187SJ20/500NCS
600	24	RS187J24/600NC	RS187J24/600SP	600	24	RS187SJ24/600SS	RS187SJ24/600NCS
750	30	RS187J30/750NC	RS187J30/750SP	750	30	RS187SJ30/750SS	RS187SJ30/750NCS
900	36	RS187J36/900NC	RS187J36/900SP	900	36	RS187SJ36/900SS	RS187SJ36/900NCS
1050	42	RS187J42NC	RS187J42SP	1050	42	RS187SJ42SS	RS187SJ42NCS
1200	48	RS187J48NC	RS187J48SP	1200	48	RS187SJ48SS	RS187SJ48NCS
1500	60	RS187J60NC	RS187J60SP	1500	60	RS187SJ60SS	

*10 sets per box

MegAlloy® Fasteners

Includes sixteen 150 mm (6") fastener strips with staples. Hinge pins not included.

Note: When ordering MegAlloy® fasteners or bulk ordering lacing with special staple lengths, you must use a green guide block (ST4-5, #50240) with your installation tool. When using loose staples, you can order a staple dispenser to speed up your installation of this product.

Ordering Number
125MA
187MA