
IXFELE

Concealed mortise hinge H2





· Area of application: For wooden frames,

for flush wooden interior doors · Door weight: ≤45 kg with 2 door hinges

≤60 kg with 3 door hinges


Opening angle: ≤180° Door width: ≤900 mm Door height: ≤2,000 mm Door thickness: ≥32 mm Size: 95 mm


Continuously 3D adjustable: Height: ±2.5 mm, side: +3/–2 mm and Adjustment facility:

closing pressure: ±1 mm

· Allen key for adjustment supplied

Installation






Note


Different recess dimensions when using hinge pockets for lining

4 door hinges must be used for door height of 2,100 mm and above.

Material	Finish	Cat. No.
	Chrome plated matt	927.91.544
	Nickel plated matt	927.91.546
	Gold coloured polished	927.91.548

Concealed mortise hinge H7





Area of application: For wooden frames,

for flush wooden interior doors

≤50 kg with 2 door hinges ≤70 kg with 3 door hinges ≤180° Door weight:


Opening angle: Door width: ≤1,000 mm Door height: ≤2,100 mm Door thickness: ≥40 mm 111.5 mm Size


Adjustment facility: Continuously 3D adjustable:

Height: ±3 mm, side: +3/-2 mm and closing pressure: ±1 mm

Fixing material supplied

Installation





Routing pattern for frame and

Note

Different recess dimensions when using hinge pockets for lining

4 door hinges must be used for door heights of 2,400 mm and above.

Material	Finish	Cat. No.
Zinc alloy	Chrome plated matt	927.91.554
	Nickel plated matt	927.91.556
	Gold coloured polished	927.91.558

►AH 4.26 Hinge pocket for lining frames

Hinge pocket for lining frames

►AH 4.26