


Type: **DILM32-XHI22**
 Article No.: **277377**
 Sales text **Contactors,aux.cont.mod.,4-pole**



With positively driven contacts; except XHIV and XHICV

Ordering information			
Connection technique			Screw terminals
Description			4 pole
Conventional thermal current $I_{th} = I_e$ AC-1 at 50 °C			
Open	$I_{th} = I_e$	A	16
Contacts			
N/O = Normally open, N/O E = Normally open (early make contact)			2 N/O
N/C = Normally closed N/C L = Normally closed (late break contact)			2 N/C
Can be combined with basic unit			DILM(C)7-10... DILM(C)9-10... DILM(C)12-10... DILM(C)15-10... DILM(C)17-10... DILM(C)25-10... DILM(C)32-10... DILMP20 DILMP32-10 DILMP45-10

Contact sequence



Notes concerning the product group

- Interlocked opposing contacts, to IEC/EN 60947–5–1 Annex L, within the auxiliary contact modules (not N/O (early make) and N/C (late break) contacts) and for the built-in auxiliary contacts of the DILM7 – DILM32
 - Auxiliary break contact can be used as mirror contact to IEC/EN 60947–4–1 Annex F (not N/C (late break) contact)
 - No auxiliary contacts can be fitted between 2 contactors.
-