


CLAMPING SETS SERIES DSM



Ready-to-use friction-locked shaft-hub connection. For motor shafts in accordance with DIN 748 with a k/6/m6 tolerance zone.

» Examples » Benefits » Function » Transmittable Forces

Order No.	Name CAD-Download	Diameter in mm			Clamping screw				Transmittable forces	
		d ₁	d ₂	L	ISO 4762	h	M _A	No.	M	F _a
			h5			mm	Nm		Nm	N
K-11301401	DSM 14.2	14	26	26	M3	3	2	4	50	7100
K-11301602	DSM 16.1	16	32	26	M4	4	5	6	95	11900
K-11301603	DSM 16.2	16	32	36	M4	4	5	6	130	16300
K-11301601	DSM 16.28	16	28	26	M3	3	2	6	66	8250
K-11301802	DSM 18.2	18	34	36	M4	4	5	6	160	17800
K-11301801	DSM 18.30	18	30	26	M3	3	2	6	92	10222
K-11301902	DSM 19.1	19	35	26	M4	4	5	6	130	13700
K-11301903	DSM 19.2	19	35	36	M4	4	5	6	200	21100
K-11301901	DSM 19.32	19	32	26	M3	3	2	6	100	10526
K-11302002	DSM 20.1	20	40	36	M5	5	10	5	190	19000
K-11302003	DSM 20.2	20	40	46	M5	5	10	5	240	24000
K-11302001	DSM 20.32	20	32	26	M3	3	2	6	108	10800