

## Ball-type quick couplings: ARS 220 - Ball-type quick coupling 220 bar NEW



| P/N        | Inlet     | Type | Weight           |    |   |
|------------|-----------|------|------------------|----|---|
| 26.2030.20 | 1/4 Bsp F | B    | 184 gr - 6,49 oz | 25 |   |
| 26.2030.25 | 1/4 Bsp M | B    | 196 gr - 6,91 oz | 25 |   |
| 26.2030.00 | 3/8 Bsp F | B    | 173 gr - 6,12 oz | 25 | ✓ |
| 26.2030.80 | M 22 F    | B    | 156 gr - 5,5 oz  | 25 | ✓ |
| 26.2040.61 | 1/4 Bsp F | A    | 69 gr - 2,43 oz  | 25 | ✓ |
| 26.2045.61 | 1/4 Bsp M | A    | 60 gr - 2,12 oz  | 25 |   |
| 26.2035.61 | 3/8 Bsp F | A    | 58 gr - 2,05 oz  | 25 | ✓ |

### Common Features

|                      |                             |
|----------------------|-----------------------------|
| Rated Pressure       | 220 bar - 22 MPa - 3200 psi |
| Permissible Pressure | 250 bar - 25 MPa - 3650 psi |
| Rated Flow Rate      | 50 l/min - 13,2 USGpm       |
| Rated Temperature    | 90 °C - 195 °F              |

### Additional Notes

Pin Ø19,9 mm - Internal hole Ø12 mm- Compatible with ARS350

### Technical Documentation

ARS220 - Technical Manual

ARS 220 - Declaration of Conformity

DIRECTIVE 2011/65/EU RoHS 2 - Category of AEE specification of the RoSH 2

IGES - ARS220 B G3/8F

IGES - ARS220 A G3/8F

STEP - ARS220 B G3/8F

STEP - ARS220 A G3/8F