




A complete, versatile system of modular containers, perfectly integrable in the SYSTEM domestic range and able to meet the high protection installation requirements of the residential, commercial and industrial sectors. The 27 COMBI range is available both in the IP40 version and in watertight versions with IP55, IP65 and IP66 degree of protection, recommended for all outdoor applications which are subjected to extreme atmospheric conditions.

Insulation class	II	Colour	Grey RAL 7035
Outer dim. LxHxD (mm)	231x82x55	IP degree	IP40
Characteristics	Halogen free	No. knockout holes Ø23	10 on sides / 2 on the bottom
Shock resistance	IK07	Compartment pre-arrangement	2
Lid screws	Stainless steel	Configuration	Module 4 x 2
Description	8 gang	Glow Wire Test	650 °C
Electrocod	0212	Thermo-pressure with ball	70 °C
Standard	EN 60670-1	Installation temperature	-25 +60 °C
Type of knockout holes	Removable with tool		


BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited resistance	Resistant	Resistant	Resistant	Limited resistance	Not resistant	Not resistant	Not resistant	Limited resistance	Resistant

DIMENSIONAL



TECHNICAL SYMBOLOGY



IP40

IK07

650 °C

70 °C

STANDARDS/APPROVALS

GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 05/04/2017

Data, measures, designs and pictures are shown only as informativ purposes, and could be changed without previous notice